



SKF 32028T130X/QDB tapered roller bearings

Bearing No. 32028T130X/QDB

| | |
|-------------------------------|----------------|
| Size | 140x210x130 mm |
| Bore Diameter | 140 mm |
| Outer Diameter | 210 mm |
| Width | 130 mm |
| d | 140 mm |
| D | 210 mm |
| T | 130 mm |
| C | 108 mm |
| a | 132 mm |
| d1 | 175 mm |
| r1 min. | 2,5 mm |
| r2 min. | 2,5 mm |
| r5 min. | 0,6 mm |
| Cb min. | 11 mm |
| db min | 152 mm |
| Db min. | 202 mm |
| ra max. | 2 mm |
| rc max. | 0,6 mm |
| Weight | 12,5 Kg |
| Basic dynamic load rating (C) | 561 kN |
| Basic static load rating (C0) | 1160 kN |
| Fatigue load limit (Pu) | 116 |
| Reference speed | 1700 r/min |
| Limiting speed | 2800 r/min |
| Calculation factor (e) | 0,46 |
| Calculation factor (Y0) | 1,4 |

32028T130X/QDB Bearing 2D drawings and 3D CAD models



NTN BEARING USA CORP.

| | |
|-------------------------|-----|
| Calculation factor (Y1) | 1,5 |
|-------------------------|-----|